LANCO
TentTech · DeconTech · FlexTank

Personal Decontamination Showers ARZ 2x2

Product Images

Short Description

All LANCO decontamination showers are especially designed to have a low weight, a small packing size, easy handling and quick set up. These are the easiest, fastest and most flexible decontamination solutions.

Our decontamination showers comply with ANSI/ISEA 113 standards.

Description

Cabin

Shower cabin made of double-sided PVC-coated polyester fabric (0.60 kg/m²), watertight, mildew-resistant, with large

transparent windows. Floor made of double-sided PVC-coated polyester fabric, watertight, mildew resistant, with anti-slip embossing (0.85 kg/m²).

Shower system

Hose arch with full cone nozzles (4.70 l/min at 3 bar per nozzle), hand shower with 1.50 m hose, stop-cock, D-coupling for water supply, C-coupling for waste water.

Frame

Inflatable frame made of airtight double-sided PVC-coated polyester fabric (1.10 kg/m²), connected with the shower cabin by a rope. The decontamination shower can be erected with compressed air cylinders or an electric blower in approximately 1 minute. A pressure relief valve prevents the frame from overfilling.

Standard

Our decontamination showers comply with ANSI/ISEA 113 standards.

Standard equipment

- Shower system with 5/10 nozzles and 1/2 Hand showers (depending on shower size)
- Storz D-coupling for water supply
- Storz C-coupling for water discharge
- Floor grid
- Carrying bag
- Pegs
- Guy ropes
- Hand pump
- Repair kit
- Manual and maintenance instructions

Additional Information

Application area	Civil Defence, Military, Decontamination and Hazardous Goods Operations, Police/Gendarmerie, Industry and commerce
Width	2.00 m
Length	2.00 m
Height	2.50 m
Nozzles	5
Hand showers	1
Hose arches	1
Packing size	0.19 m³
Weight	approx. 44 kg