LANCO
TentTech · DeconTech · FlexTank

Professional Folding Tent FZ PRO 84

Product Images

Short Description

Pop-up tents that take 60 seconds to set up and require no additional tools or trained staff due to their integrated easy set-up mechanism.

Description

Frame

The tent frame is made entirely of anodized aluminum rectangular tubes with aluminum connectors. To protect the tent roof from chafing, plastic caps are attached to all parts and screws in contact with the fabric.
The frame is delivered fully pre-assembled and only needs to be pulled apart during set up. The tubes snap into place automatically.

Roof and side walls

The tent skin is made of one-sided PU-coated polyester fabric 550dtex (240 g/m²); Flame retardant, waterproof and mildew resistant. The roof is connected to the frame by means of Velcro. After the first time the tent is erected, the roof can remain

fastened to the folded frame for quick subsequent deployments.
Optional side walls are made of one-sided PU-coated polyester fabric 280dtex (165 g/m²); Flame retardant, waterproof and mildew resistant. The side walls are cut for an average passage height of 2.12 m.

Options and accessories

- Partition walls
- Side windows
- Rain gutters
- Sealing flaps between tents
- Connection clamps for tents
- Optional additional legs
- Ballast weights
- Modular flooring
- Heating
- Lighting
- Lettering/branding

Additional Information

Application area	Industry and commerce, Promotion agencies, Party – Event
Base area	32.00 m²
Width	4.00 m
Length	8.00 m
Headroom	2.10 m
Eaves height	2.40 m (2.20 - 2.60 m)
Ridge height	3.85 m (3.65 - 4.00 m)
Packing size	205 x 75 x 45 cm
Weight	76.00 kg