



Medical and Accommodation Aluminum Frame Tents - SG 18

Product Images



Short Description

SG tents come in 14 standard configurations and 10 different areas of applications. No special tools are required for setup, they are modular and easy to interconnect.

Description

Standard

Tent with entrance in the front gable (toggle closing), window 60 x 40 cm with exterior shutter in back gable, aluminium frame and accessories.

Frame

The frame system consists of anodized aluminium tubes, diameter 40 mm. The connectors and base plates are made of an aluminium alloy.

- Wall thickness of 1.5 mm of the material AL Mg 4,5 Mn.
- Yield strength: $R_{p0,2} = 330-340 \text{ N/mm}^2$

- Ultimate strength: Rm = 350-370 N/mm2
- Peg, 20 mm diameter, hot-dip galvanised iron with top forged on, 700 g, 300 mm long
- T-peg, galvanised iron, 300 mm long
- Peg with hook, galvanised steel, 300 mm long

Tent skin

LANCO tents are made of LANCO heavy- duty fabric.LANCO-heavy-duty fabric is permeable to the air, rot-resistant, water pressure proof laminated and is extremely tearproof as well as highly protec-tive against UV-rays.

Fabric:

Twisted cotton-polyester 50%/50%Yarn

Options:

- Connecting unit, chimney passage, divisibilty with loop closing, canopy, partition walls, roll-up facili-ty of one side or one panel
- Window, tent skin
- Window, inner cabin
- Roll-up facility one panel
- Second entrance

Additional Information

Application area	Military
Base area	17.70 m²
Width	4.08 m
Length	5.34 m
Eaves height	1.61 m
Ridge height	2.25 m
Packing size	0.20 m³
Weight	63.00 kg