



## Multi Purpose Aluminum Frame Tents - SG 301

### Product Images



### Short Description

SG tents come in 14 standard configurations and 10 different areas of applications. No special tools are required for setup, they are modular and easy to interconnect.

### Description

#### Standard

Tent with aluminium frame and accessories. Tent skin made of LANCO-heavy-duty fabric. Entrance in front and back gable, gables are detachable and divisible, walls can be rolled-up to the eaves, 4 windows 60 x 40 cm incl. exterior shutter in panel 2 and 3, tent bag, accessory bag and bag for the frame.

#### Frame

The frame system consists of anodized aluminium tubes, diameter 40 mm. The connectors and base plates are made of an aluminium alloy (all poles with a length of 1.94 m).

Wall thickness of 1.5 mm of the material AL Mg 4,5 Mn.

Yield strength:  $R_{p0,2} = 330-340 \text{ N/mm}^2$

Ultimate strength:  $R_m = 350-370 \text{ N/mm}^2$

Peg, 20 mm diameter, hot-dip galvanised iron with top forged on, 700 g, 300 mm long  
T-peg, galvanised iron, 300 mm long  
Peg with hook, galvanised steel, 300 mm long

Tent skin

LANCO tents are made of LANCO heavy-duty fabric twisted cotton-polyester 50%/50%Yarn.  
LANCO-heavy-duty fabric is permeable to the air, rot-resistant, water pressure proof laminated and is extremely tearproof as well as highly protective against UV-rays.

Options:

- Connecting unit, chimney passage, divisibility with loop closing, canopy, partition walls, roll-up facility of one side or one panel
- Window, tent skin
- Window, inner cabin
- Roll-up facility one panel
- Second entrance

Additional Information

Application area	Military
Base area	29.40 m²
Width	4.90 m
Length	6.00 m
Eaves height	1.94 m
Ridge height	2.70 m
Packing size	120 x 100 x 74 cm
Weight	107.00 kg