



# **Folding Rescue Tents - FRZ 33**

### **Product Images**



## **Short Description**

LANCO folding rescue tents provide you with reliable support everyday in emergencies; developed and manufactured to the highest standards of quality and functionality.

## **Description**

LANCO FRZ tents can be fully assembled in a matter of minutes. Only two people are required for the complete assembly and erection with side walls, tent floor and anchoring to the ground with steel t-pegs.

#### **Frame**

The tent frame is made entirely of anodized aluminum rectangular tubes with aluminum connect-ors. The frame is delivered fully pre-assembled and only needs to be pulled apart during set up. The tubes snap into place automatically. The poles can be extended by increments of 10 cm, resulting in passage heights of 1.92 m to 2.32 m.

#### **Roof and Side Walls**

The tent roof is made of flame retardant, waterproof and mildew resistant one-sided PU-coated polyester fabric 550dtex (240  $g/m^2$ ). The roof is connected to the frame by means of Velcro. After the first time the tent is erected, the roof can remain fastened to the folded frame for quick subsequent deployments.

The side walls are made of flame retardant, waterproof and mildew resistant one-sided PU-coated polyester fabric 550dtex (240  $g/m^2$ ). They are equipped with gray PVC mud flaps and fastening rods connecting them to the tent floor.

#### Floor

The floor is made of light gray double-sided coated PVC polyester fabric. The fabric is waterproof, flame retardant, mildew resistant and requires little maintenance. Bottom fastening rods made of gal-vanized steel are integrated at the corners. The connection to the tent is secured by pushing the fas-tening rods through the PVC fabric loops. This prevents the floor from slipping and gives the tent greater stability.

The roofs for our FRZ tents are available in 11 colors. However, side walls are only offered in gray.

#### **Additional Information**

Application area	Military
Base area	9.00 m <sup>2</sup>
Width	3.00 m
Length	3.00 m
Headroom	2.10 m
Eaves height	2.40 m
Ridge height	3.27 m
Packing size	1.63 x 0.60 x 0.45 m